Manufacturer/Supplier:	Vandex Isoliermittel-Gesellschaft mbH, D-21493 Schwarzenbek		
Product number:	005		
Trade name:	VANDEX BB 75		
Printing date:	01. 04. 2006	Reviewed on: 01. 04. 2006	Page: 1/7

01. Identification of preparation and company

Trade name VANDEX BB 75 * Use of preparation Waterproofing slurry Manufacturer/Supplier Vandex Isoliermittel-Gesellschaft m.b.H. Industriestrasse 19-23 D-21493 Schwarzenbek +49 4151 89 15-0 Phone: +49 4151 89 15 50 Fax: General Information +49 41 51 89 15 31 (Laboratory, Vandex Isoliermittel GmbH, Germany) Phone: Phone: +41 32 626 36 36 (Technical Department, Vandex International AG, Switzerland) * Emergency telephone GIZ Nord Poisons Centre, Germany +49 551 19240 Phone:

02. Composition/Information on ingredients

* Chemical characterization

Preparation of cement, silica sands and additives * <u>Hazardous ingredients</u>

Ingredients	CAS no.	EINECS no.	Concentration	Hazard symbols	R-phrases
Cement	65997-15-1	266-043-4	50–75%	Xi, irritant	R 38, 41
(≤ 2 ppm CrVI)					

03. Hazards identification

Classification

Xi irritant

R 38 Irritating to skin.

- R 41 Risk of serious damage to eyes.
- Particular information pertaining specific risk for humans and environment

Prolonged contact with the product may cause skin disorders / chemicals burns

* Further information

The content of hexavalent chromium in the cement is reduced to ≤ 2 ppm. The chromate reduction is effective within the shelf life and when properly stored. Please refer to chapter 7.

04. First aid measures

* Inhalation

Remove person from exposure. In case of irritation of respiratory system seek medical advice.

Skin contact

After contact with skin wash immediately with plenty of water. If irritation persists seek medical advice.

* Eye contact

In case of contact with the eyes rinse immediately with plenty of water (eye lid wide open) for at least 10 minutes and seek medical advice urgently.

Ingestion

Drink plenty of water. Seek medical advice.

05. Fire-fighting measures

Suitable extinguishing media

Adapt to surrounding fire; product is not combustible.

* Special exposure hazards arising from the preparation itself, combustion products, resulting gases

Avoid extinguishing water entering into water courses, drains or ground water.

In contact with extinguishing water an alkaline solution – which can cause irritation – is produced.

* Special protective equipment for fire-fighters

Use self-contained breathing apparatus

Manufacturer/Supplier:	Vandex Isoliermittel-Gesellschaft mbH, D-21493 Schwarzenbek			
Product number:	005			
Trade name:	VANDEX BB 75			
Printing date:	01. 04. 2006	Reviewed on: 01. 04. 2006	Page: 2/7	

06. Accidental release measures

* Personal precautions

Avoid contact with skin and eyes. Do not breathe dust. Refer to chapter 8. <u>Environmental precautions</u> Avoid uncontrolled contact with water. Avoid uncontrolled discharge into environment after contact with water. Do not allow to enter into

water courses, drains or ground water.

Methods for cleaning up/collecting

Clean up dry. Avoid dust formation.

07. Handling and storage

* Information for safe handling Keep out of the reach of children. Avoid dust formation and dust deposit. Avoid contact with skin and eyes. Do not breathe dust. Refer to chapter 8 – Personal protective equipment Information about protection against explosions and fires

Not applicable.

* Requirements to be met by storerooms and containers

Store protected from humidity in unopened, undamaged original packaging. Shelf life: 12 months

* Information about separation of incompatible products Keep away from food, drink and animal feedingstuffs.

08. Exposure controls and personal protection

Exposure limit values (Great Britain)

65997-15-1	Portland cement	EH40 / 2005: OEL 8-hour TWA	10	ma/m3
	inhalable dust	EH40 / 2005. UEL 0-HOUL TWA	10	mg/m³
	respirable dust	EH40 / 2005: OEL 8-hour TWA	4	mg/m³

OEL = Occupational Exposure Limit; TWA = Time Weighted Average; Observe country specific occupational exposure limits * Occupational exposure controls

Avoid dust formation. Avoid creating dust. Provide appropriate ventilation or local exhaust ventilation. If it is not possible to reduce exposure levels to below exposure limit values with ventilation use appropriate respirator according to national regulations.

* Personal protective equipment

General protective and hygiene measures

Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Use appropriate skin protection products.

* Respiratory protection

Use approved dust mask/respirator

* Hand protection

Use suitable impervious protective gloves

Eye protection

Use tightly fitting safety glasses.

* Skin protection

To avoid skin contact use suitable protective clothing.

* Environmental exposure controls

Do not allow to enter into water courses, drains or ground water.

09. Physical and chemical properties

* General information

grey powder
odourless
and environmental information
not applicable
not applicable
not applicable
not applicable
not applicable
approx. 1.4 kg/l
c) up to 1.5 g/l
11 – 13.5

Manufacturer/Supplier: Vandex Isoliermittel-Gesellschaft mbH, D-21493 Schwarzenbek

Product number:005Trade name:VANDEX BB 75Printing date:01. 04. 2006

Reviewed on: 01. 04. 2006

Page: 3/7

10. Stability and reactivity

Conditions to avoid

- Avoid contact with humidity.
- * Materials to avoid
- Acid
- * <u>Hazardous decomposition products</u> Not applicable.

11. Toxicological information

Irritant/Corrosive effects

Irritating to skin and mucous membranes. Risk of serious damage to eyes. Prolonged contact with the product may cause skin disorders / chemicals burns.

* Sensitization

As long as material is used within shelf life sensitization is not to be expected. Refer to chapter 3+7.

12. Ecological information

* Ecotoxicity

Eco-toxicological effect only possible in case of unintended release of big quantities in contact with water due to increased pH value. Product is slightly water pollutant (self assessment). Do not allow to enter into water courses, drains or ground water.

- * Mobility
- Refer to ecotoxicity
- * Persistence and degradability
- No data available for the preparation
- * Bioaccumulative potential
- No data available for the preparation
- * Other adverse effects

No data available for the preparation

13. Disposal considerations

Product/Preparation

Recommendation

Clean up dry, not contaminated material can be re-used. Hardens after contact with water, hardened material can be disposed of as construction and demolition waste – concrete (EWC-Code 170101). The listed waste number according to the European Waste Code (EWC) is a recommendation. The final classification has to be done together with the local waste disposal company / authority. Contaminated packaging

Recommendation

Contaminated packaging must be emptied of all residues and can be recycled following appropriate cleaning. Avoid dust formation. Uncleaned packaging must be disposed of in accordance with official local regulations (EWC-Code 150105 composite packaging (Paper/PE-foil)).

14. Transport information

Not a dangerous good according to the transport regulations.

15. Regulatory information

Classification according to EEC directives

Danger symbol and danger designation

- Xi irritant
- Hazard-determining components of labelling
- Cement
- * Risk-phrases
- R 38 Irritating to skin.
- R 41 Risk of serious damage to eyes
- * Safety-phrases
 - S 2 Keep out of the reach of children.
 - S 22 Do not breathe dust
 - S 24/25 Avoid contact with skin and eyes.
 - S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 - S 37/39 Wear suitable gloves and eye/face protection

Manufacturer/Supplier:	Vandex Isoliermittel-Gesellschaft mbH, D-21493 Schwarzenbek			
Product number:	005			
Trade name:	VANDEX BB 75			
Printing date:	01.04.2006	Reviewed on: 01, 04, 2006	Page: 4/7	

16. Other information

* Sources of key data used to compile the data sheet:

EC Directive 67/548/EC resp. 99/45/EC as amended in each case

EC Directive 91/155/EC as amended in each case

EC Directive 2001/58/EC as amended in each case

EC Directive 2000/39/EC as amended in each case

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

* Relevant R-phrases (chapter 2):

R 38 Irritating to skin.

R 41 Risk of serious damage to eyes

Alterations/supplements to the previous version are marked with *

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Prod Trad	ufacturer/Supplier: uct number: e name:	150 VANDEX CEMELAST I		
Print	ing date:	01.08.2006	Reviewed on: 01.08.2006 / Version 3	Page: 05/07
01.	Trade name VANDEX CEMEL/ * Use of prepara Mixing liquid for dr * Manufacturer/S Vandex Isoliermitt Industriestrasse 19 D-21493 Schwarz Phone: +49 419 Fax: +49 419 Fax: +49 419 Phone: +49 419 Phone: +41 32 * Emergency tele GIZ Nord Poisons	tion y mortars Supplier el-Gesellschaft m.b.H. 9–23 enbek 51 89 15-0 51 89 15 50 ation 51 89 15 31 (Laboratory, 626 36 36 (Mrs. Ch. Pr ephone	n and company Vandex Isoliermittel GmbH, Germany) idal, Vandex International Ltd, Switzerland)	
02.	Composition/Info Chemical charac Chemical nature: Hazardous compo		nts Water based dispersion of butadiene styrene copolymer none according to EU directive 1999/45/EC	
03.			none according to EU directive 1999/45/EC	
04.	Skin contact Prolonged contact symptoms persist Eye contact May cause tempor Ingestion	OUT ir. In severe cases seek mo may cause irritation. Remo rary irritation. Irrigate with w	edical attention ove contaminated clothing. Wash thoroughly with soap and wa vater for minutes holding eyelid open. attention. Do not induce vomiting.	ater. Seek medical attention if
05.	Fire-fighting means The product is water	<u>isures</u> ter based and is not combu	istible.	
06.	Methods for clea Large spillages sh	tions recautions ntering soil, natural waters ning up/collecting	and drains. nped into a receiving vessel. Small spillages should be absorbe	ed on inert absorbant. For
07.	Handling and sto Information for s No special precau Information for s	afe handling tions necessary. Observe g	good housekeeping practice. Keep workplace well ventilated.	

Information for safe storage Store between +5 °C and +35 °C protected from frost and direct sunlight. Do not use storage vessels or pipework made of aluminium.

Prod	ufacturer/Supplier: uct number:	Vandex Isoliermittel-Ge		D-21493 Schwarzenbek	
	e name: ng date:	VANDEX CEMELAST I 01.08.2006		viewed on: 01.08.2006 / Version 3	Page: 06/07
08.	Exposure controls * Exposure limit vi None according to E * Occupational exp The product may co Provide appropriate * Personal protect Respiratory protect If spraying product vi Hand protection Impermeable gloves Eye protection record Skin protection In case of severe sp Hygiene measure	U directive 88/379/EC. <u>cosure controls</u> ntain low levels of volatile ventilation or load exhaus <u>ive equipment</u> ction vithout local exhaust vent recommended mmended plashing wear waterproof of	e organic compount st ventilation. Wh ilation, wear app overalls and boot	nds or ammonia which may evapora ere product is dried or sprayed local ropriate respiration protection. s. Wash with soap and water after h	ate during application and drying. exhaust ventilation is recommended.
09.	Physical and cher Image Form: liquid Colour: white Odour: faint aror Relevant safety da Vapor pressure: Relative density: Solubility in water: pH-value: Viscosity:	natic	approx. 23 hPa 0.9 – 1.1 insoluble, but m 9.0 – 10.0 100 – 1000 mPa	scible in all proportions	
10.	Stability and react The product is stabl Incompatible materi	e under recommended st	orage conditions none	(Section 7)	
11.	Toxicological info Long term experience		icates no danger	to health when properly handled un	der industrial conditions.
12.	Ecological informa Degradation / elimin The prod Bioaccumulation: Ecotoxic effects:	ation:	ated from water No evidence fo	n after 2 days (OECD302B) : 98%. by abiotic processes, e.g. adsorptior r bioaccumulation not classified as Dangerous for the B	-
13.		Dn Id not be discharged dire		waterways without treatment. Dispo er containing product should be treat	sal of product and packaging should ed in a separation and biological
14.	Transport informa The product is not c	<mark>tion</mark> lassified as Dangerous fo	r Carriage.		

Manufacturer/Supplier:	Vandex Isoliermittel-Gesellschaft mbH, D-21493 Schwarzenbek			
Product number:	150			
Trade name:	VANDEX CEMELAST LIQUID			
Printing date:	01.08.2006	Reviewed on: 01.08.2006 / Version 3	Page: 07/07	

 Labelling according to EU directive 1999/45/EC:

 Symbol
 Not subject to labelling

 National regulations:

 Germany:
 Water hazard class
 WGK = 1, VwVwS, Kenn. Nr. 662

 Information given in this Material Safety Data Sheet does not constitute the user's own workplace risk assessment

16. * Other information

Alterations/supplements to the previous version are marked with *

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.